

## IROKO TIMBER - MAINTENANCE & CARE

Please follow this step-by-step guide when re-applying oil, as regularly as needed.

- Remove all cushions.
- Ensure to protect rope and webbing where applicable with masking tape.
- Sand all timber areas lightly or more aggressively, either by hand or machine, with 120 grid sandpaper until the original timber is exposed.
- Clean and brush off all remaining dust.
- Apply oil to a mutton cloth and cover all the areas of the timber surfaces evenly with a film of oil (we recommend ProNature's outdoor oil).
- Leave on for about 15 minutes to allow the oil to penetrate.
- Then wipe off all excess oil with a clean cloth until touch dry. There should be no excess oil left behind.

**Dispose of all used cloths by saturating them in water.  
Failure to do so will result in combustion - leading to fire.**

The next maintenance routine will depend on how quickly the timber changes due to its exposure to the elements. Frequent maintenance will ensure less effort to rejuvenate the items the next time. The furniture will continue to serve its function for years to come.

Please feel free to send us photos or ask our advice at any time.

+385 (0)1 2087356 | [info@blocoutdoor.hr](mailto:info@blocoutdoor.hr) | [blocoutdoor.co](http://blocoutdoor.co)

Business Park 1A, Radnička cesta 1a, 10000, Zagreb, Croatia